



LAN Cable U/UTP Cat.6 EconLine

Technical Features

Category 6 ISO/IEC 11801

4x2x23AWG CCA Solid Wire

U/UTP Unshielded Twisted Pair Cable

PVC Jacket


Color: Gray

Technical Drawings

n° Pairs.xΦmm	Conductor Resistance Ω/km	Resistance Unbalance	Cap. between cond. pair nF / 100m	Velocity of Propagation %	Impedance Ω	ΦExt. (Appvox) mm
4x2x0.57	max.112	max.4%	/	69	100±15	6.0±0.1

Frequency (MHz)	RL ≥dB	ATT ≤dB/100m	NEXT ≥dB	DELAY ≤ns/100m	PS NEXT ≥dB	EL FEXT ≥dB/100m	PS EL FEXT ≥dB/100m
4	31.48	3.52	78.26	471.18	63.72	74.19	68.66
8	34.11	5.01	72.26	466.28	55.33	76.3	67.13
10	36.38	5.61	66.46	465.01	56.32	87.16	69.86
16	38.55	7.14	77.00	462.79	60.22	71.88	64.07
20	40.09	8.02	68.24	461.86	54.86	68.56	63.27
25	43.96	9.01	66.41	461.09	52.39	73.95	67.61
31.25	44.35	10.11	61.70	460.38	49.77	69.44	65.41
62.5	42.84	14.53	76.59	459.09	46.47	74.49	60.86
100	50.40	18.75	57.59	457.69	45.32	59.08	56.94
200	32.57	27.29	58.97	456.71	39.88	46.02	54.32
250	28.02	31.06	55.06	456.44	38.35	38.08	37.83

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Eca	EN50575:2014 A1:2016
Dangerous substances	None	



Technical Specification:

- Conductor TCCA: 0.57 ± 0.01 mm
- Insulation HDPE: 1.00 ± 0.05 mm
- Identification of pairs
 - 1 pair: Blue-White/Blue
 - 2 pair: Orange-White/Orange
 - 3 pair: Green-White/Green
 - 4 pair: Brown-White/Brown
- Filler: PE
- Ripcord: Yes
- Sheath: 6.0 ± 0.1 mm PVC
- Color: Gray
- Bending radius $\geq 8 \times$ Diameter (mm) Installation
- Storage temperature: $-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$

www.logilink.com



RoHS
compliant



Length	Part no.	EAN Code
100 m	CPV0033	4052792006094
305 m	CPV0034	4052792006100

Package Contents

LAN Cable U/UTP Cat.6 EconLine x 1

Packaging Informations(CPV0033)

Packing Dimension	260 x 260 x 100mm
Packing Weight	2.8kg
Carton Dimension	540 x 280 x 320mm
Carton Q'ty	6pcs
Carton Weight	17.1kg

Packaging Informations(CPV0034)

Packing Dimension	390 x 390 x 220mm
Packing Weight	8.3kg
Carton Dimension	475 x 400 x 400mm
Carton Q'ty	2pcs
Carton Weight	20kg





2direct GmbH – Langenstück 5 – 58579 Schalksmühle

CE- DECLARATION OF PERFORMANCE

No. 101117_4

Unique product - type identification code LogiLink Cable Cat.6 U/UTP (PV0033,CPV0034)
Intended use High-speed data transmission cabling
Importer/Distributor 2direct GmbH
Langenstück 5
D-58579 Schalksmühle

Notified body VDE
Notified body no. 0366*

Classification Report No 5022677/16-1
Issue number 1
Date of issue 2017-09-06

System/s of AVCP 3

Test method and test number EN 60332-1-2

Reaction to fire performance

Essential Characteristic	Performance	Harmonized techn. Standard
Fire behaviour	Eca	EN 50575:2014 + A1:2016
Hazardous substances	NPD	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Schalksmühle, March 16th., 2017

Place and date of issue

Signature (Wilfried Grohnert)

Bank national:
Volksbank im Märkischen Kreis eG
BLZ: 447 615 34
Kto.[EUR] 118 547 300
Kto.[USD] 118 547 315

Bank international:
Volksbank im Märkischen Kreis eG
BIC/SWIFT: GENODEM1NRD
IBAN: DE27447615340118547300
IBAN: DE10447615340118547315

2direct GmbH
Langenstück 5
D-58579 Schalksmühle
Tel. +49-2351-66887-0
Fax. +49-2351-66887-29

UST Id.-Nr. DE813146449
Homepage: www.2direct.de
Register: HRB 4819, Iserlohn
WEEE-Reg.-Nr.: DE81077960
GF: W. Grohnert, J. Alberts