

Apacer AS340

Fast and Furious – Reliable Solution for

Computer System Optimization

Apacer AS340 is a class-leading, gaming-oriented solid state drive (SSD) offering your PC to operate at the fastest speed. Designed in SATAIII 6.0 Gb/s interface, the drive can deliver outstanding performance up to 490 MB/s data transfer speed, highly suitable to serve as operating system boot drive, storage media of important data, or perfect solution for budding gamers on a budget. The mechanical design of AS340 conforms to the latest requirements of SATAIII 6.0 Gb/s interface. Hence, power efficiency wise, AS340 supports SATA power management modes which greatly cut power consumptions to make it an environmental and economical storage drive than traditional hard disk drives.

AS340 boasts built-in advanced Wear Leveling and ECC functions and supports Windows 7 TRIM command. These not only extend SSD life and improve operation stability, but also maintain long-term performance.

Available in 120GB and 240GB, AS340 can meet the demand of different users. Meanwhile, Apacer publishes specially designed SSD Widget software which allows users to examine the SSD status as well as instant firmware update. With the advantages of performance and stability mentioned above, AS340 is proved to be the best companion for PC and laptop upgrade.

Features:

- SATA 6.0 Gb/s interface compliance
- Outstanding read/write performance
- Supports SATA Power Management
- Powerful ECC engine correcting up

to 72bit/1KB Supports S.M.A.R.T. commands

• Supports NCQ/TRIM commands



Applications

- PC/NB for general storage
- Operating system boot drive for PC/NB
- Network servers
- Industrial PCs
- Graphic and video applications
- Kiosk, POS and automation.
- Multimedia
- Gaming







© 2016 Apacer Technology Inc.



General Product Specifications

Specifications					
Interface	SATA 6.0 Gb/s interf	ace			
SATA 6.0 Gbps Burst Speed	600 MB/s				
Capacity ¹	120 GB, 240 GB,480GB,1024GB				
Capacity	Capacity	120 GB	240 GB	480GB	
Performance ²	Sequential Read	550	550	550	
(Unit: MB/s)	Sequential Write	500	490	450	
Endurance	Capacity	120 GB	240 GB	480GB	
	TBW	70TB	140TB	280TB	
Form Factor	2.5 inch				
NAND Flash Media	TLC				
ECC	Up to 72bit/1KB				
MTBF	1,500,000 hours (approx.)				
Operating Voltage	5V ± 5%				
Power	Capacity	120 GB	240 GB	480GB	
consumption ³	Active	1450	1260	1430	
(Unit: mW)	Idle	325	320	320	
Dimension	100.00mm(L) x 69.85mm(W) x 7.00mm(H)				
Weight	75g				
Reliability Features	S.M.A.R.T, Wear Leveling, TRIM, NCQ				
Tomporatura	Operating	0°C to 70°C			
Temperature	Storage	-40°C to 85°C			
Humidity	RH 90% under 40°C				
Shock ⁴	1,500G/0.5ms				
Vibration ⁴	80 – 2000Hz/20G				
Acoustic	OdB				
Warranty	3 years				
Package Content	Retail package				
Certifications	RoHS, CE, FCC				

Global Offices Taiwan (HO)

Apacer Technology Inc.

1F., No.32, Zhongcheng Rd., Tucheng Dist., New Taipei City Taiwan, R.O.C Tel: +886-2-2267-8000 Fax: +886-2-2267-2261 amtsales@apacer.com

U.S.A

Apacer Memory America, Inc.

46732 Lakeview Blvd., Fremont, CA 94538 Tel: 1-408-518-8699 Fax: 1-510-249-9551 sa@apacerus.com

<u>sa@apacerus.coi</u> _

<u>Japan</u>

Apacer Technology Corp.

5F, Matsura Bldg., Shiba, Minato-Ku Tokyo, 105-0014, Japan Tel: 81-3-5419-2668 Fax: 81-3-5419-0018 jpservices@apacer.com

<u>Europe</u>

Apacer Technology B.V.

Science Park Eindhoven 5051 5692 EB Son, The Netherlands Tel: 31-40-267-0000 Fax: 31-40-267-0000#6199 sale@apacer.nl

<u>China</u>

Apacer Electronic (Shanghai)

Co., Ltd

Room D, 22/FL, No.2, Lane 600, Jieyun Plaza, Tianshan RD, Shanghai, 200051, China Tel: 86-21-6228-9939 Fax: 86-21-6228-9936 sales@apacer.com.cn

<u>India</u>

Apacer Technologies Pvt Ltd

Unit No.201, Brigade Corner, 7th Block Jayanagar, Yediyur Circle, Bangalore – 560082, India Tel: 91-80-4152-9061 Fax: 91-80-4170-0215 <u>sales india@apacer.com</u>

Apacer

Rev. 1.2

² Performance results may vary from flash configurations or host system settings. Test results are based on ATTO platform, and of all the results, only the least impressive performance is given for reference. Normally the read/write speeds in actual scenarios can be better than the values here.

³ Power consumption was measured at 5.0V and for 240 GB capacity only. The results may vary from flash configurations or host system settings.

⁴ Shock and vibrations are subject to change without notice.

© 2016Apacer Technology Inc.

¹ Unformatted. Theoretically, 1GB=1,000,000,000 Bytes. Under operating systems, the capacity might appear to be less than the theoretical capacity because the calculation in OS is based on 1 GB = 1024 MB / 1MB =1024KB and a minority of the capacity is reserved for maintenance purposes.



Apacer Rev. 1.2

Ordering Information

Capacity	Bulk	Distributor/Retailer
120 GB	AP120GAS340G	AP120GAS340G-1
240 GB	AP240GAS340G	AP240GAS340G-1
480 GB	AP480GAS340G	AP480GAS340G-1

Revision History

Version	Description	Date
1.0	Official release	6/22/2016
1.1	Added technical notes for performance results	7/6/2016
1.2	Add 480GB	4/28/2018

Apacer Technology Inc.

1F., No.32, Zhongcheng Rd., Tucheng Dist., New TaipeiCity Tel: +886-2-2267-8000 Fax: +886-2-2267-2261

www.apacer.com

Copyright ©2016 Apacer Technology Inc. All Rights Reserved. Information in this document is subject to change without prior notice. Apacer and the Apacer logo are trademarks or registered trademarks of Apacer Technology Inc. Other brands, names, trademarks or registered trademarks may be claimed as the property of their respective owners.

© 2016 Apacer Technology Inc.