

3MP HD Outdoor Pan & Tilt Wi-Fi Camera

Uho-P2A-M3F4D



















Features

- High quality image with 3MP, 1/3" CMOS sensor
- 2304*1296@20fps in the main stream
- Ultra 265, H.265, H.264
- Support digital WDR (Wide Dynamic Range)
- Built-in Mic & Speaker, support two-way audio, offer better interaction
- Support sound and light warning, makes warning and alarming more noticeable
- Smart IR, up to 30 m (98 ft) IR and 10 m (32 ft) warm light distance, suitable for more scenes
- Self-contained bracket, support two kinds of mounting
- Supports 512 GB Micro SD card
- Wi-Fi connection and easy installation
- IP66 ingress protection
- The front face is made of grapheme, which has better heat dissipation and more environmental protection

1



Specifications

Model	Uho-P2A-M3F4D	
Camera		
Max Resolution	3 MP	
Sensor	1/3.0" CMOS	
Min. Illumination	Colour: 0.005Lux (F1.6, AGC ON)	
	0 Lux with IR on	
Day/Night	IR-cut filter with auto switch (ICR)	
Shutter	Auto/Manual, 1 ~ 1/100000s	
S/N	>52 dB	
WDR	DWDR	
Lens		
Digital Zoom	4X	
Focal Length	4.0 mm	
Iris Type	Fixed	
Iris	F1.6	
Field of View (H)	90.5 °	
Field of View (V)	44.4°	
Field of View (D)	111.3°	
Lens Type	Fixed	
DORI		
DORI Distance (Lens)	4.0mm	
DORI Distance (Detect)	73.5 (241.0ft)	
DORI Distance (Observe)	29.4 (96.4ft)	
DORI Distance (Recognize)	14.7 (48.2ft)	
DORI Distance (Identify)	7.3 (24.1ft)	
Illuminator		
Illumination Distance (IR)	30 m (98.4 ft)	
Illumination Distance (Warm Light)	10 m (32.8 ft)	
Wavelength	850 nm	



IR On/Off Control	Auto/Manual		
Video			
Video Compression	Ultra 265, H.265, H.264		
Frame Rate	Main Stream: 3MP (2304*1296), Max 20fps;		
	Sub Stream: 640*360, Max 20fps;		
Video Bit Rate	128 Kbps to 2048 Kbps		
U-code	Support		
OSD	Up to 2 OSDs		
Privacy Mask	Support (only NVR)		
ROI	Up to 8 areas		
Video Stream	Dual Streams		
Image			
White Balance	Auto, Outdoor, Fine Tune, Sodium Lamp, Locked, Auto2		
Digital Noise Reduction	2D/3D DNR		
Smart IR	Support		
Flip	Normal, Flip Vertical, Flip Horizontal, 180 °		
Dewarping	N/A		
HLC	N/A		
BLC	N/A		
Defog	Digital Defog		
Events			
Basic Detection	Human Body Detection, Motion Detection, Audio Detection		
General Function	IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication, HTTP Authentication		
Intelligent	Intelligent		
Auto Tracking	Support		
Audio			
Audio Compression	G.711U, G.711A		
Audio Bitrate	64 Kbps		
Two-way Audio	Support		
Suppression	Support		




Sampling Rate	8 kHz	
Storage		
Edge Storage	Micro SD, up to 512 GB	
Network Storage	ANR	
Network		
Wi-Fi	2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna	
Protocols	IPv4, TCP, UDP, DHCP, RTSP, DNS, DDNS, NTP, HTTP	
Compatible Integration	API	
Client	Uniarch Client, Uniarch app	
Web Browser	Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+	
Wi-Fi		
Wireless Standards	IEEE802.11b/g/n	
Frequency Range	2.4 GHz to 2.4835 GHz	
Channel Bandwidth	20 MHz Support	
Modulation Mode	802.11b: CCK, QPSK, BPSK	
Modulation Mode	802.11g/n: OFDM/HT	
Wi-Fi Security	64/128-bit WEP, WPA-PSK/WPA2-PSK	
Transmit Power	802.11b: 17±1.5 dBm@11 Mbps802.11g: 14±1.5 dBm@54 Mbps802.11n: 12.5±1.5 dBm@150 Mbps	
Receive Sensitivity	802.11b: -90 dBm@11 Mbps (Typical)802.11g: -75 dBm@54 Mbps (Typical)802.11n: -74 dBm@150 Mbps (Typical)	
Transmission Rate	802.11b: 11 Mbps802.11g: 54 Mbps802.11n: up to 150 Mbps	
PTZ		
Pan Range	0 °~ 345 °	
Pan Speed	1 %s ~ 40 %s	
	Preset speed: 40 %s	
Tilt Range	0°~90°	
Tilt Speed	1 %s ~ 30 %s	
	Preset speed: 30 %s	
Number of Presets	20	
Interface		
Audio I/O	N/A	



Alarm I/O	N/A	
Built-in Mic	Support	
Built-in Speaker	Support	
WIFI	Support	
Network	1 ×RJ45 10 M/100 M Base-TX Ethernet	
Certification		
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130)	
	FCC (FCC 47 CFR part15 B)	
RF	FCC ID (FCC CFR 47 part15 C)	
	CE RED (EN 301 489-1, EN 301 489-17, EN 300 328, EN 62311)	
Safety	CE LVD (EN 62368-1)	
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);	
Protection	IP66 (IEC 60529)	
General		
Power	DC 12V ±25%	
Power Interface	Ø5.5 mm coaxial power plug	
Dimensions	Φ110mm*110mm*151mm (Φ4.3"x 4.3"x 6.0")	
Weight	0.38kg (0.84lb)	
Working Environment	-30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤95% RH (non-condensing)	
Storage Environment	-30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤95% RH (non-condensing)	
Surge Protection	4 KV	
Reset Button	Support	
LED Indicator	1, red/blue	



Dimensions



Accessories

TR-JB05-A-IN

TR-UP06-B-IN

TR-UP06-C-IN

 $Small \ Bullet \ Junction \ Box(Support \ wiring \ from \ be \\ hind, Square)$

Bullet Pole Mounting B racket

Pole Mounting Bracket for Bullet Junction
Box Only









TR-A01-IN

TR-UC08-C

NPT 3/4" Waterproof Cable Gland Bullet&Dome Corner Mounting Bracket





Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

http://www.uniview.com

©2024-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.



VERIFICATION OF COMPLIANCE

Verification No.: KSCR240900175501ATC

Applicant: Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou Address of Applicant:

City, 310051, Zhejiang Province, China

Zheijang Uniview Technologies Co., Ltd. Manufacturer:

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou Address of Manufacturer:

City, 310051, Zhejiang Province, China

IP Camera **Product Description:**

Model No.: Uho-P2A-M3F4D, Uho-P2A-xxxxxxxx-yyyyyyyy-zzzz ("x" can be 0-9, A-

Z, a-z or blank, denoting difference in interface, "y" can be 0-9,A-Z,az or blank, denoting performance difference, "z" can be 0-9,A-Z,a-

z or blank, denoting target regional, "-" is optional)

Test Standards: EN 300 328 V2.2.2

> EN 301 489-1 V2.2.3 EN 301 489-17 V3.2.4 EN IEC 62311:2020

Test Report Number(s): KSCR240900175501; KSCR240900175502; KSCR240900175503

Based on a review of the test report(s) detailed above, this apparatus meets the requirements of above standards. The product is in conformity with the essential requirements of Article 3.1 (a) the protection of the health and with/without safety, 3.1 (b) an adequate level of electromagnetic compatibility and 3.2 effective use of the spectrum of 2014/53/EU.

The CE mark can be used, under the responsibility of the manufacturer, after completion of an EU Declaration of Conformity and compliance with all relevant EU Directives.

Terry Hou

Technical Manager Compliance Certification Services (Kunshan) Inc.

This document is issued by the Company under its General Conditions of Service accessible at .htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent



Date: 2024-09-23

Compliance Certification Services (Kunshan) Inc. No.10 Weiye Road, Development Zone, Kunshan, Jiangsu, China

www.sgsgroup.com.cn Member of the SGS Group (SGS SA)



VERIFICATION OF COMPLIANCE

KSCR250300035101ATC Verification No.:

Applicant: Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou Address of Applicant:

City, 310051, Zhejiang Province, China

Zhejiang Uniview Technologies Co., Ltd. Manufacturer:

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou Address of Manufacturer:

City, 310051, Zhejiang Province, China

IP Camera Product Description:

Uho-P2A-M3F4D, Uho-P2C-M4F4, Uho-P2A-xxxxxxxx-yyyyyyyy-zzzz, Model No.:

Uho-P2C-xxxxxxxx-yyyyyyyy-zzzz ("x" can be 0-9, A-Z, az or blank, denoting difference in interface, "y" can be 0-9,A-Z,a-z or blank, denoting performance difference, "z" can be 0-9,A-Z,a-

z or blank, denoting target regional, "-" is optional)

EN 55032: 2015+A11:2020+A1:2020 Test Standards:

EN 50130-4: 2011 +A1:2014

EN 61000-3-3: 2013+ A1:2019+A2:2021 EN IEC 61000-3-2: 2019+A1:2021+A2:2024

Test Report Number(s): KSCR250300035101

This Verification of EMC Compliance has been granted to the applicant based on the results of the tests, performed by laboratory of Compliance Certification Services (Kunshan) Inc. on the sample of the above-mentioned product in accordance with the provisions of the relevant specific standards under Directive 2014/30/EU. The CE mark can be used, under the responsibility of the manufacturer, after completion of an EU Declaration of Conformity and compliance with all relevant EU Directives.

Technical Manager

jurisdiction issues defined therein.

Compliance Certification Services (Kunshan) Inc.

Terry Hou


This document is issued by the Company under its General Conditions of Service accessible at http://www.sgs.com/terms and conditions.htm. Attention is drawn to the limitation of liability, indemnification and

Compliance Certification Services (Kunshan) Inc. No.10 Weiye Road, Development Zone, Kunshan, Jiangsu, China

ation Se/

www.sqsqroup.com.cn Member of the SGS Group (SGS SA)

Date: 2025-03-21





VERIFICATION OF COMPLIANCE

SUES2503000355AT No.:

Applicant: Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District,

Hangzhou City, 310051, Zhejiang Province, China

Manufacturer: Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District,

Hangzhou City, 310051, Zhejiang Province, China

IP Camera **Product Name:** IP Camera **Product Description:**

Uho-P2A-M3F4D, Uho-P2C-M4F4, Model No.:

Uho-P2A-xxxxxxxx-yyyyyyy-zzzz, Uho-P2C-xxxxxxxx-yyyyyyyy-zzzz,

(where x, y, z may be 0-9, A-Z, a-z or blank, "-" may be blank)

Trade Mark:

uniarch Rating: 12 V d.c., 1,0 A

Protection against Electric Shock: Class III Additional Information (if any): None

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: EN IEC 62368-1:2020+A11: 2020

as shown in the

Test Report Number(s): SUES240900138402

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards.



2025-05-09

SGS-CSTC Standards Technical Services Co., Ltd.

This document is issued by the Company under its General Conditions of Service accessible at conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

CSTC Standards Technical Services Co., Ltd. 16F, Century Yu Hui Mansion, No.73, Fucheng Road, Haidian District, Beijing, 100142, CHINA Member of the SGS Group (SGS SA)