

# USB-C to USB-C 3A/60W Braided Cable

L501 35465 35441 35254 35334 65248 65245

65246 65247

## Features

- 3A big current, 60W Fast Charging
- 480Mbps Data transfer
- Support PD and SCP
- Braided Cable
- 10000+ times plug and play

## Specifications

- \* Line length: 0.15-3 meters
- \* wire external: TPE
- \* Core Material: Tin-Coated Copper
- \* Shielded Aluminum Foil + Metal Braided Mesh
- \* Wire cores: 0.15-2 meters: 4 cores + 1 floor \n3 meters: 4 cores + 5 floors
- \* Current Capacity: 3A (MAX)
- \* pin for USB-C: 12-pin
- \* Plug: USB-C/M White Core (94V-0) Terminal Gold-plated 15U" Stainless Steel Enclosure Nickel-plated Except for the black model, which has a white core.
- \* Chip Model: /
- \* USB-C plug-and-play operations: 10,000 times
- \* Capacitor Parameters: /
- \* Interface Version/Data Transfer: USB 2.0/480 Mbps
- \* Charging Power: 5V/3A, 9V/2A, 9V/3A, 15V/2A, 15V/3A, 20V/3A (MAX)
- \* Charging Protocol: PD/SCP
- \* Flame Retardant Grade GB/T 5169.23-2008
- \* Operating temperature/storage temperature: 0~45° C / -15~70° C
- \* Environmental requirements comply with EU RoHS 2.0, REACH, SVHC, Appendix 17, POPs; California 65, TSCA; and China RoHS.

