


4MP Fixed IR Mini Bullet Network Camera

IPC-B134-AF28(40)-ECO



Features

- High quality image with 4 MP, 1/3.0" CMOS sensor
- 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@25/30 fps; 1080P (1920 × 1080)@25/30 fps
- Supports accurate human body detection 2.0
- Ultra 265, H.265, H.264
- 2D/3D DNR (digital noise reduction)
- ROI (region of interest) ensures image quality in areas of interest with low bandwidth
- Smart IR, up to 30 m (98.4 ft.) IR distance
- 3-axis
- Built-in mic
- Wide temperature range: -30 °C to 60 °C (-22 °F to 140 °F)
- PoE (IEEE 802.3af)
- IP67


Specifications

Model	IPC-B134-AF28-ECO		IPC-B134-AF40-ECO
Camera			
Max Resolution	4 MP		
Sensor	1/3.0" CMOS		
Min. Illumination	Color: 0.003 Lux (F2.0, AGC ON), 0 Lux with IR		
Day/Night	IR-cut filter with auto switch (ICR)		
Shutter	Auto/Manual, 1 to 1/100000 s		
Adjustment Angle	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°		
S/N	> 52 dB		
WDR	DWDR		
Lens			
Focal Length	2.8 mm	4.0 mm	
Iris	F2.0		
Field of View (H)	97°	74.6 °	
Field of View (V)	54.9°	40.5°	
Field of View (D)	111.9 °	89.1 °	
DORI			
DORI Distance (Lens)	2.8 mm	4 mm	
DORI Distance (Detect)	63.0 m (206.7 ft.)	90.0 m (295.3 ft.)	
DORI Distance (Observe)	25.2 m (82.7 ft.)	36.0 m (118.1 ft.)	
DORI Distance (Recognize)	12.6 m (41.3 ft.)	18.0 m (59.1 ft.)	
DORI Distance (Identify)	6.3 m (20.7 ft.)	9.0 m (29.5 ft.)	
Illuminator			
Supplemental Light	IR		
Illumination Distance (IR)	30 m (98.4 ft.)		
Wavelength	850 nm		
IR On/Off Control	Auto/Manual		
Video			
Video Compression	Ultra 265, H.265, H.264		
H.264 Code Profile	Baseline profile, Main profile, High profile		
Frame Rate	Main Stream: 4 MP (2560 × 1440), max. 25 fps; 3 MP (2304 × 1296), max. 30 fps; 1080P (1920 × 1080), max. 30 fps		
	Sub Stream: 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps		
Video Bit Rate	128 Kbps to 6144 Kbps		
U-code	Support		
OSD	Up to 4 OSDs		
Privacy Mask	Up to 4 areas		
ROI	Support		
Video Stream	Dual streams		
Image			

Smart Illumination	Support
White Balance	Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2, Area white balance
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
Flip	Normal, Flip vertical, Flip horizontal, 180°
Dewarping	N/A
HLC	Support
BLC	Support
Defog	Digital defog
Events	
Basic Detection	Motion detection, Audio detection, Human body detection 2.0
General Function	Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication
Audio	
Audio Compression	G.711U, G.711A
Audio Bitrate	64 Kbps
Two-way Audio	N/A
Suppression	Support
Sampling Rate	8 kHz
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, DNS, DDNS, NTP, UPnP, HTTP, QoS, RTCP, RTMP, SNMP
Compatible Integration	ONVIF (Profile S, Profile T) , SDK
User/Host	Up to 32 users. 3 user levels: administrator, common user and operator
Security	Strong Password, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, WSSE and Digest Authentication for ONVIF, Log Encrypted Export
Client	APP, Uniarch client
Web Browser	Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+
Interface	
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	Support
Built-in Speaker	N/A
WIFI	N/A
Network	1 × RJ45 10 M/100 M Base-TX Ethernet
Video Output	N/A
Certification	
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B)
Safety	CE LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);
Protection	IP67 (IEC 60529)
General	

Power	PoE (IEEE 802.3af)
Power Consumption	Max. 2.5 W
Power Interface	N/A
Dimensions	140 mm × 61 mm × 65 mm (5.5" × 2.4" × 2.6") (L × W × H)
Weight	0.14 kg (1.32 lb.)
Material	Plastic
Working Environment	-30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)
Storage Environment	-30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)
Surge Protection	4 KV
Reset Button	N/A
Web Client Language	4 Languages: English, Russian, Spanish, Vietnamese

Dimensions



Accessories

TR-JB05-A-IN

Small Bullet Junction Box(Support wiring from behind,Square)



TR-UP06-B-IN

Bullet Pole Mounting Bracket



TR-A01-IN

NPT 3/4" Waterproof Cable Gland



TR-UP06-C-IN-V2

Pole Mounting Bracket for Bullet Junction Box Only



TR-UC08-C-V2

Bullet&Dome Corner Mounting Bracket



Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.

VERIFICATION OF COMPLIANCE

Verification No.: KSEM250600152601ATC

Applicant: Zhejiang Uniview Technologies Co., Ltd.

Address of Applicant: No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Manufacturer: Zhejiang Uniview Technologies Co., Ltd.

Address of Manufacturer: No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Product Description: IP Camera

Model No.: IPC-B125-APF28K, IPC-B124-APF28K, IPC-B128-APF28K, IPC-B233-APF40W, IPC-B134-AF40-ECO, IPC-B134-AF40-DL-ECO, IPC-B245-ADF40K-WP, IPC-B245-xxxxxxx-yyyyyyy-zzz, IPC-B128-xxxxxxx-yyyyyyy-zzz, IPC-B233-xxxxxxx-yyyyyyy-zzz, IPC-B124-xxxxPxxxx-yyyyyyy-zzz, IPC-B125-xxxxPxxxx-yyyyyyy-zzz, IPC-B132-xxxxxxx-yyyyyyy-zzz, IPC-B242-xxxxxxx-yyyyyyy-zzz, IPC-B244-xxxxxxx-yyyyyyy-zzz, IPC2312LE-xxxxxxx-yyyyyyy-zzz, IPC2314LE-xxxxxxx-yyyyyyy-zzz, IPC2122LB-xxxxxxx-yyyyyyy-zzz, IPC-B134-xxxxxxx-yyyyyyy-zzz ("x, y, z" can be 0-9, A-Z, a-z or blank, "-" may be blank)

Test Standards: EN 50130-4: 2011+A1:2014
EN 55032: 2015+A11:2020+A1:2020
EN 61000-3-3: 2013+A1:2019+A2:2021
EN IEC 61000-3-2: 2019+A1:2021+A2:2024

Test Report Number(s): KSEM250600152601

This Verification of EMC Compliance has been granted to the applicant based on the results of the tests, performed by laboratory of Compliance Certification Services (Kunshan) Inc. on the sample of the above-mentioned product in accordance with the provisions of the relevant specific standards under Directive 2014/30/EU. The CE mark can be used, under the responsibility of the manufacturer, after completion of an EU Declaration of Conformity and compliance with all relevant EU Directives.



Terry Hou
Technical Manager

Compliance Certification Services (Kunshan) Inc.

Date: 2025-06-06



This document is issued by the Company under its General Conditions of Service accessible at http://www.sgs.com/terms_and_conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Compliance Certification Services (Kunshan) Inc.
No.10 Weiye Road, Development Zone, Kunshan, Jiangsu, China
www.sgsgroup.com.cn
Member of the SGS Group (SGS SA)

VERIFICATION OF COMPLIANCE

No.: SUES2510002219ATA01
Applicant: Zhejiang Uniview Technologies Co., Ltd.
No. 369, Xietong Road, Xixing Sub-district, Binjiang District,
Hangzhou City, 310051, Zhejiang Province, China
Manufacturer: Zhejiang Uniview Technologies Co., Ltd.
No. 369, Xietong Road, Xixing Sub-district, Binjiang District,
Hangzhou City, 310051, Zhejiang Province, China
Product Name: IP Camera
Product Description: IP Camera
Model No.: See Page 2
Trade Mark: 
Rating: See page 2
Protection against Electric Shock: Class III
Additional Information (if any): VOC SUES2510002219AT dated on 2025-12-11 is no longer
valid since this VOC SUES2510002219ATA01 dated on
2026-03-26 issued. Revised content see report.
Sufficient samples of the product have been tested and found to be in conformity with
Test Standard: EN IEC 62368-1:2020+ A11:2020
as shown in the
Test Report Number(s): SUES251000221902

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards.

Dan Xie

Technical Manager

SGS-CSTC Standards Technical Services Co., Ltd.

2026-03-26

This document is issued by the Company under its General Conditions of Service accessible at http://www.sgs.com/terms_and_conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS-CSTC Standards Technical Services Co., Ltd.
16F, Century Yu Hui Mansion, No.73, Fucheng Road, Haidian District, Beijing, 100142, CHINA
www.sgsgroup.com.cn
Member of the SGS Group (SGS SA)

No.:

SUES2510002219ATA01

Model list:

- (1) IPC-B122-xxxxPxxxx-yyyyyyyyy-zzz, IPC-B124-xxxxPxxxx-yyyyyyyyy-zzz, IPC-B125-xxxxPxxxx-yyyyyyyyy-zzz, IPC-B112-xxxxPxxxx-yyyyyyyyy-zzz, IPC-B113-xxxxPxxxx-yyyyyyyyy-zzz, IPC-B114-xxxxPxxxx-yyyyyyyyy-zzz, IPC-B233-xxxxxxx-yyyyyyyyy-zzz, IPC-B312-xxxxxxx-yyyyyyyyy-zzz, IPC-B314-xxxxxxx-yyyyyyyyy-zzz
- (2) IPC-B123-xxxxPxxxx-yyyyyyyyy-zzz
- (3) IPC-B128-xxxxxxx-yyyyyyyyy-zzz
- (4) C-50B-xxxxxxx-yyyyyyyyy-zzz, C-80B-xxxxxxx-yyyyyyyyy-zzz
- (5) Uho-B1R-xxxxxxx-yyyyyyyyy-zzz
- (6) IPC-B233-xxxxxxx-yyyyyyyyy-zzz
- (7) IPC-B132-xxxxxxx-yyyyyyyyy-zzz, IPC2122LB-xxxxxxx-yyyyyyyyy-zzz
- (8) IPC-B242-xxxxxxx-yyyyyyyyy-zzz, IPC-B244-xxxxxxx-yyyyyyyyy-zzz, IPC2312LE-xxxxxxx-yyyyyyyyy-zzz, IPC2314LE-xxxxxxx-yyyyyyyyy-zzz
- (9) IPC-B134-xxxxxxx-yyyyyyyyy-zzz
- (10) IPC2314LB-xxxxxxx-yyyyyyyyy-zzz, IPC2312LB-xxxxxxx-yyyyyyyyy-zzz, IPC-B232-xxxxxxx-yyyyyyyyy-zzz, IPC-B234-xxxxxxx-yyyyyyyyy-zzz

('x' can be 0-9, A-Z, a-z or blank; 'y' can be 0-9, A-Z, a-z or blank; 'z' can be 0-9, A-Z, a-z or blank;

'-' may be blank)

Rating:

- (1) 12 Vd.c., 1,0A, POE 48 Vd.c., 0,25A;
- (2) 12 Vd.c., 1,0A;
- (3) 12 Vd.c., 1,0A, POE 48 Vd.c., 0,25A;
- (4) 12 Vd.c., 1,0A, POE 48 Vd.c., 0,25A;
- (5) 12 Vd.c., 1,0A;
- (6) 12 Vd.c., 1,0A, POE 48 Vd.c., 0,25A
- (7) POE 48 Vd.c., 0,25A
- (8) 12Vd.c., 1,0A; POE 48 Vd.c., 0,25A
- (9) POE 48V,0,25A
- (10) POE 48V,0,25A

Dan Xie

Technical Manager

SGS-CSTC Standards Technical Services Co., Ltd.

2026-03-26

This document is issued by the Company under its General Conditions of Service accessible at http://www.sgs.com/terms_and_conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS-CSTC Standards Technical Services Co., Ltd.
16F, Century Yu Hui Mansion, No.73, Fucheng Road, Haidian District, Beijing, 100142, CHINA
www.sgsgroup.com.cn
Member of the SGS Group (SGS SA)